



AN ISO CERTIFIED COMPANY



Stalwart Ultra High Pressure Hydraulic Hose

Extreme duty high pressure hydraulic line with a **Scuff Tuff** highly abrasion resistant MSHA approved cover. This flexible multispiral hydraulic hose has a reduced bend radius and force to bend.

Stalwart Ultra High Pressure Hydraulic Hose

MEETS ISO 18752-CC AND EXCEEDS SAE100 R15

CORE: Synthetic rubber, resistant to most hydraulic fluids.

REINFORCEMENT: Four or six spiral layers of high tensile steel wire.

COVER: **Scuff Tuff** abrasion and ozone resistant synthetic rubber. MSHA approved. **10X the abrasion resistance of a standard hydraulic hose.**

TEMPERATURE RANGE: -40 degrees F to +250 degrees F

PART NUMBER	DASH SIZE	NOMINAL HOSE I.D. (INCHES)	NOMINAL HOSE O.D. (INCHES)	WORKING PRESSURE (PSI)	MIN. BURST PRESSURE (PSI)	MIN. BEND RADIUS (INCHES)
72006-80080	-6	0.38	0.79	6,090	24,360	2.56
72008-80080	-8	0.50	0.90	6,090	24,360	3.54
72010-80080	-10	0.63	1.04	6,090	24,360	3.94
72012-80080	-12	0.75	1.21	6,090	24,360	4.72
72016-80080	-16	1.00	1.48	6,090	24,360	5.91
72020-80080	-20	1.25	1.99	6,090	24,360	15.75
72024-80080	-24	1.50	2.26	6,090	24,360	18.11
72032-80080	-32	2.00	2.81	6,090	24,360	21.26



MFC HOME OFFICE: SAINT PAUL, MINNESOTA

305 Bridgepoint Drive, Suite 400
South Saint Paul, MN 55075
Tel: 651.645.7522 800.351.9069
Fax: 651.645.8259



PEORIA, ILLINOIS

817 N.E. Adams Street
Peoria, IL 61603
Tel: 309.674.6570
Fax: 309.674.6471



GRAND RAPIDS, MINNESOTA

1201 S.E. 7th Avenue
Grand Rapids, MN 55744
Tel: 218.999.9069
Fax: 218.999.9031




MILWAUKEE, WISCONSIN

N83W12650 Stratton Circle, Suite 300
Menomonee Falls, WI 53051
Tel: 262.754.5522
Fax: 262.754.5525



GALESBURG, ILLINOIS

698 US Hwy 150 East
Galesburg, IL 61402
Tel: 309.342.6171
Fax: 309.342.6946



APPLETON, WISCONSIN

2310 West College Avenue
Appleton, WI 54914
Tel: 920.733.7223
Fax: 920.738.7228