



AN ISO 9001:2015 COMPANY



# Endurance Extreme Duty Hydraulic Hose

Extreme duty hydraulic line with a highly abrasion resistant MSHA approved cover. This problem solving hydraulic hose has a compact outside diameter, tight bend radius, and is rated to 1 million impulse cycles.

## Endurance Extreme Duty Hydraulic Hose 2SN-K

EXCEEDS DIN EN 857 2SC / SAE 100R16-S

**CORE:** Oil resistant synthetic rubber

**REINFORCEMENT:** Two braids of high tensile steel wire.

**Exceeds 1 Million Impulse Cycles.**

**COVER:** Abrasion and ozone resistant synthetic rubber. MSHA approved. **10X the abrasion resistance of a standard hydraulic hose.**

**TEMPERATURE RANGE:** -40 degrees F to +212 degrees F (250 degrees F intermittent)

PART NUMBER	DASH SIZE	NOMINAL HOSE I.D. (INCHES)	NOMINAL HOSE O.D. (INCHES)	WORKING PRESSURE (PSI)	MIN. BURST PRESSURE (PSI)	MIN. BEND RADIUS (INCHES)
72004-80070	-4	0.25	0.53	6,525	26,100	1.77
72005-80070	-5	0.31	0.59	6,090	24,350	2.36
72006-80070	-6	0.38	0.67	5,585	22,340	2.76
72008-80070	-8	0.50	0.82	5,075	20,300	3.54
72010-80070	-10	0.63	0.93	4,025	16,820	5.12
72012-80070	-12	0.75	1.09	4,060	16,240	6.30
72016-80070	-16	1.00	1.40	3,000	12,000	8.27